

CHAIN FASTENERS TECHNICAL DATA SHEET

VERSION 4.1 | 09/05/2022



Before installing, please ensure you have downloaded the latest version of this TDS by scanning this code.





Contents

Introduction	3
Overview	
Application	
Mechanical properties	
Chain hidden decking clip	
Accessories	
Packaging	8
Disclaimer and copyright	9



Introduction

Manufacturers details

Product name: Chain collated decking clip for grooved composite or timber deck boards

Manufacturing information: Eva-Last

Room 1203, 12/F

Tower 333 Canton Road,

Tsimshatsui,

Hong Kong, China

 Emergency Contact:
 +86 021 53397986

 Product information:
 +27 10 593 9220

Email: info@eva-last.com

Website: www.eva-last.com

Overview

A single Chain collated decking clip strip consists of a magazine of 15 clips with pre-loaded screws. Screws are available for both timber, and similar, as well as metal substructure substrates. Each clip consists of a stainless-steel skeleton wrapped in a polymer coating, this polymer also forms the base and collation for the clips.

Application

Used as a hidden fastener between timber and composite grooved boards.

· Compatible with deck board grooves as detailed below.



• Typical resultant gap between boards as detailed bellow.




- Compatible with timber or composite joists of a minimum profile height of 38 mm and width of 38 mm.
- · Compatible with metal joists of a minimum profile height of 32 mm and width of 25 mm.

09/05/2022 Page 3 of 16



Applications with timber and composite substructure substrates




Part		Feature	Detail		
$\left[\frac{1}{4}^n\right]$		Screw dimensions	M4.2 x 42 mm		
- Comm		Screw material	Stainless steel 316 (A4)		
		Screw coating	Dark brown epoxy (~ 20 μm thick)		
	Screw	Head type	Pan head		
		Drill point type	Type 17 (self-drilling)		
		Effective thread length	30 mm to 33 mm		
		Pre-drilling hole size (if applicable)	2.5 mm		
		Clip dimensions	17 x 7 x 19 mm		
		Clip insert material	Stainless steel 316L (A4) or 304 (A2)		
	Clip	Clip coating, base, collation and insert	Black Polypropylene (minimum ~200 µm thick)		
		Clip base width	5.8 mm		
6mm		Clip base expansion buffer width	0.3 mm		

09/05/2022 Page 4 of 16



Applications with metal substructure substrates



Part	Feature	Detail	
[1-] 	Screw dimensions	M4.2 x 32 mm	
- mod	Screw material	Carbon Steel - C1022	
	Screw coating	Dark brown epoxy. (~ 20 μm thick)	
Screw	Head type	Pan head	
i es	Drill point type	Pre-Drilling point	
	Effective thread length	30 mm to 31 mm	
	Pre-drilling hole size (if applicable)	3.3 mm	
	Clip dimensions	17 x 7 x 19 mm	
$\begin{bmatrix} \frac{1}{3} \end{bmatrix}$ $\begin{bmatrix} \frac{1}{4} \end{bmatrix}$	Clip insert material	Stainless steel 316L (A4) or 304 (A2)	
	Clip coating, base, collation and insert	Black Polypropylene (minimum ~200 µm thick)	
[<u>s</u>]	Clip base width	5.8 mm	
- " - 	Clip base expansion buffer width	0.3 mm	

09/05/2022 Page 5 of 16




Mechanical properties

Timber clip screw

The timber clip screw torque and tensile resistance was tested according to the GB/T 3098.21-2014 test standard by China Component Testing (CCT). The screw withdrawal results are based on internal tests conducted on a 305 stainless steel version of the same screw.

Specification	Results	Units	Units
Ultimate torque	2.6	Nm	Tests conducted by CCT.




Specification	Results	Units	Notes
Average tensile failure load - timber screw and clip	5.2	kN	The clips deformed under load, but no failure occurred.
Average tensile failure load - metal screw and clip	5.1	kN	The clips deformed under load, but no failure occurred.

09/05/2022 Page 6 of 16



Accessories



Part	Feature	Detail		
	Hand tool dimensions	364 x 52 x 53.5 mm		
	Clip capacity	1 to 15		
Hand tool	Material	Aluminium body, nylon caps and zinc galvanised steel ancillary parts		
nand tool	Coating	Black powder coated		
	Default depth setting	6 mm groove foot height		
	Adjustable depth plate	9 mm groove foot height (3 mm adjustment plate)		
	Bit Type	Torx 15		
	Bit length	50 mm		
	Bit material	S2 alloy steel		
Bit	Effective stop out depth	19.5 mm		
	Expected lifespan for timber applications	Estimated 40 to 50 m ²		
	Expected lifespan for metal applications	Estimated 8 to 10 m ²		
	Packaging	Bit included in hand tool box and sold separately		

09/05/2022 Page 7 of 16



Packaging

 $Both \ the \ timber \ and \ metal \ application \ versions \ of \ the \ Chain \ Collated \ decking \ clip \ is \ available \ in \ various \ packaging \ options.$

Pack	Quantity of strips	Quantity of clips	Approximate coverage (m² per pack)	Box dimensions (mm)	Box masses (kg)	Note	
150 Series pack (Timber series)	— 10 strips	150 clips		50 x 90 x 290 —	0.8	Single box of 10 strips of 15 clips.	
150 Series pack (Metal series)			6 to 9		0.8		
900 Series pack (Timber series)	— 60 strips	900 clips	36 to 54	150 x 180 x 290 —	4.4	Single sleeve of 6 of the 150 Series packs.	
900 Series pack (Metal series)					4.7		
3 600 Master carton (Timber version)	— 240 strips	r version)				17.6	Single box of 4
3 600 Master carton (Metal version)		3 600 clips	144 to 216	300 x 360 x 290 —	18.8	of the 900 Series packs.	
Hand tool	1 Han	d tool	N/A	65 x 77 x 377	0.6		

09/05/2022 Page 8 of 16



Disclaimer and copyright

Document disclaimer

The provided information is offered in good faith as accurate but without guarantee. Eva-Last makes no warranties or representations of any kind (express or implied) about the accuracy, adequacy, currency, or completeness of the information, or that it is necessarily suitable for the intended use.

Compliance with this document does not guarantee immunity from breach of any statutory requirements, building codes or relevant standards. The final responsibility for the correct design and specification rests with the designer and, for its satisfactory execution, with the contractor. Appropriate warnings and safe handling procedures should be provided to handlers and users.

While most data have been compiled from research, case histories, experience and testing, small changes in the environment can produce marked differences in performance. The decision to use a material, and in what manner, is made at your own risk. The use of a material and method may therefore need to be modified to its intended end use and environment.

Eva-Last, its directors, officers or employees shall not be responsible for any direct, indirect, or special loss or damage arising from, or as a consequence of, use of, or reliance upon, any information contained in this document or other documents referenced herein. Eva-Last expressly disclaims any liability which is based on or arises out of the information or any errors, omissions or misstatements herein.

Drawing disclaimer

All dimensions and specifications are offered in good faith as accurate but without guarantee. The information captured herein may not contain complete details. Eva-Last makes no warranties or representations of any kind (express or implied) about the accuracy, adequacy, currency, or completeness of the information, or that it is necessarily suitable for the intended use.

Compliance with this document does not guarantee immunity from breach of any statutory requirements, building codes or relevant standards. The final responsibility for the correct design and specification rests with the designer and, for its satisfactory execution, with the contractor.

Utilisation disclaimer

Legislation may differ between jurisdictions. Before installing any Eva-Last product, ensure that the application is rational and complies with the local regulations and building codes. Wherever necessary, consult a suitably qualified professional. Be sure to comply with material manufacturer specifications. Where manufacturers and building codes differ, revert to the building code requirements. Check that your choice of product is suitable for its intended application. For further product specification and information visit www.eva-last.com.

Copyright

If reprinted or reproduced or utilised in any form Eva-Last should be acknowledged as the source of the information.

Eva-Last periodically updates the information contained in this document as well as that of the Eva Last documents that have been referenced herein. Before using this document, please refer to the Eva-Last website (www.eva-last.com) for the most up-to-date documents.

Contact information

Eva-Last

Room 1203, 12/F Tower 333 Canton Road, Tsimshatsui, Hong Kong, China

Emergency Contact: +86 021 53397986 **Product information:** +27 10 593 9220

Email: info@eva-last.com
Website: www.eva-last.com

09/05/2022 Page 9 of 16

